



Sauer Compressors USA

Dependable Compressors!

2 STAGE AIR COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP 15L	2/2	100-580 PSI	8-10 SCFM	4.69-6.97 HP	5.7-7.1 SCFM	3.1-3.6 HP
WP 22L	2/2	100-580 PSI	12-14 SCFM	6.3-7.6 HP	8.24-9.18 SCFM	4-4.7 HP
WP 33L	2/2	100-508 PSI	18.7-19.3 SCFM	8.9-10.9 HP	11.2-12.7 SCFM	5.9-7.2 HP
WP 45L	2/2	100-580 PSI	31.4-35.7 SCFM	13.2-16 HP	20-23.2 SCFM	11-13.4 HP
WP 65L	2/2	100-580 PSI	41-47 SCFM	17.6-21.5 HP	26.8-30.4 SCFM	14.6-17.8 HP
WP 146L	2/2	87-145 PSI	88-92 SCFM	32-35 HP	62-65 SCFM	22-23.5 HP
WP 226L	2/2	87-145 PSI	152.7-154.4 SCFM	51.4-55.7 HP	112.1-113.7 SCFM	30.4-33 HP

3 STAGE AIR COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP 66L	3/3	580-1160 PSI	73 SCFM	31 HP	49 SCFM	21 HP
WP 81L	3/3	200-640 PSI	52.3-57.3 SCFM	23.5-27.3 HP	34.9-38.4 SCFM	15.7-18.4 HP
WP 101L	3/3	200-640 PSI	65.3-71.1 SCFM	29.4-34.3 HP	43.5-47.2 SCFM	19.3-22.5 HP
WP 121L	3/3	200-640 PSI	78.4-90 SCFM	37.5-43.3 HP	52.4-60.2 SCFM	22.9-26.8 HP
WP 126L	3/3	580-1160 PSI	75.9-77.1 SCFM	43.6-46.9 HP	53.2-53.5 SCFM	33.8-35.5 HP
WP 206L	3/3	580-1160 PSI	159-164 SCFM	87-98 HP	91-103 SCFM	53.6-67 HP
WP 151L	3/3	200-640 PSI	94-102.3 SCFM	45.8-53.5 HP	62.6-69 SCFM	27.7-32.4 HP
WP 271L	3/4	200-640 PSI	144-158 SCFM	62.7-71 HP	98.8-105.7 SCFM	41.6-46.9 HP
WP 311L	3/4	200-640 PSI	184-207.7 SCFM	85.2-102.4 HP	125.1-136 SCFM	49.8-58.1 HP
WP 3232	3/3	1015-3335 PSI	N/A	N/A	6-8 SCFM	9 HP
WP 3215	3/3	1450-4000 PSI	10-11.2 SCFM	10.3-11.7 HP	6.4-7.4 SCFM	5.1-6 HP

4 STAGE AIR COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP 4325	4/4	1450-6090 PSI	14-15 SCFM	14.3-16.4 HP	9.5-10.6 SCFM	9.7-11.1 HP
WP 4331	4/4	1670-5800 PSI	22.7-24 SCFM	21-23.6 HP	15.3-15.9 SCFM	13.6-16.5 HP
WP 4341	4/4	1670-5800 PSI	38.5-42.4 SCFM	29.9-34.8 HP	26.1-29 SCFM	18.8-22.7 HP
WP 4351	4/4	1670-5075 PSI	70-76 SCFM	55.6-67 HP	46.8-50.4 SCFM	36.3-42.6 HP



Sauer Compressors USA

Dependable Compressors!

2 STAGE WATER COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP100	2/2	100-435 PSI	60.8-65.1 SCFM	28.5-31.7 HP	41-44 SCFM	19.1-21.3 HP
WP 200	2/2	100-435 PSI	103-110 SCFM	47.8-53.1 HP	70.8-75.8 SCFM	31.4-34.9 HP
WP 240	2/2	100-435 PSI	124-133.5 SCFM	58.8-65.4 HP	86-92.4 SCFM	38.8-43.1 HP
WP 400	2/3	100-435 PSI	217-231 SCFM	98.4-109.3 HP	153-164 SCFM	63-70 HP

3 STAGE WATER COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP 3100	3/3	500-1450 PSI	111.8 SCFM	75.1-83.1 HP	77.1 SCFM	46.9-55 HP

4 STAGE WATER COOLED

MODEL	STAGES/ CYLINDERS	MIN-MAX PRESSURE	Motor Speed= 1770 RPM		Motor Speed= 1150 RPM	
			CAPACITY F.A.D.	REQUIRED POWER	CAPACITY F.A.D.	REQUIRED POWER
WP 5500	4/4	2500-5075 PSI	22-42 SCFM	40 HP	NA	NA
WP 5000	4/4	2500-5075 PSI	48-90 SCFM	75 HP	NA	NA

BOOSTERS

MODEL	STAGES/ CYLINDERS	MIN-MAX INLET	MIN-MAX OUTLET	Motor Speed= 1770 RPM	
		PRESSURE	PRESSURE	CAPACITY F.A.D	REQUIRED POWER
WP 33LB	1/2	58-116 PSI	290-580 PSI	33-58 SCFM	9-15 HP
WP 65LB	1/2	58-116 PSI	290-580 PSI	76-136 SCFM	16-28 HP
MP 6000/4000	2, 3, or 4/6	0-260 PSI	200-6000 PSI	up to 1110 SCFM	150-290 HP

Contact Information

Sauer Compressors USA, Inc.
64 Log Canoe Circle
Stevensville, MD 21666

Phone: 410.604.3142
Fax: 410.604.3209
sales@sauerusa.com